



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

Dated

16 JAN 2002





The Patent Office

1/77

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

05MAR01 E610908-1 D01070  
F01/7700 0.00-0105343.8  
The Patent Office  
Cardiff Road  
Newport  
Gwent NP9 1RH

1.	Your reference	P2886.A2/RAM		
2.	Patent application number (The Patent Office will fill in this part)	<b>0105343.8</b>		- 3 MAR 2001
3.	Full name, address and postcode of the or of each applicant ( <i>underline all surnames</i> )	Visteon Global Technologies, Inc Suite 728, Parklane Towers East One Parklane Boulevard, Dearborn Michigan 48126-2490 USA 7940307001 Michigan		
	Patents ADP number ( <i>if you know it</i> )			
	If the applicant is a corporate body, give the country/state of its incorporation			
4.	Title of the invention	Component Carrier		
5.	Name of your agent ( <i>if you have one</i> )	DUMMETT COPP		
	"Address for service" in the United Kingdom to which all correspondence should be sent ( <i>including the postcode</i> )	25 THE SQUARE MARTLESHAM HEATH IPSWICH IP5 3SL		
	Patents ADP number ( <i>if you know it</i> )	6379001		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and ( <i>if you know it</i> ) the or each application number	Country	Priority application number ( <i>if you know it</i> )	Date of filing ( <i>day / month / year</i> )
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing ( <i>day / month / year</i> )	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? ( <i>Answer 'Yes' if:</i> a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	Yes		

## Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 13

Claim(s) 4

Abstract 1

Drawing(s) 3 + 3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

One

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11. I/We request the grant of a patent on the basis of this application.

DUMMETT COPP

Signature

*Robert McLean*

Date

2 March 2001

12. Name and daytime telephone number of person to contact in the United Kingdom
- Robert McLean  
01473 660600

### Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

## Component Carrier

The present invention relates to a carrier for an electronic component, and to use of the carrier to mount an electrical component having one or more connection pins to a circuit board.

During manufacture of an electrical assembly comprising a circuit board with one or more electronic sub-assemblies mounted on the circuit board, it is often necessary for electrical connections from the sub-assemblies to be inserted into through-plated holes or connector sockets on the board. To improve assembly efficiency, it is common practice to provide a funnel shaped entry or "lead in" to the sockets. This allows for a certain amount of error in the component alignment during assembly. This solution is effective in many cases, but may not always be sufficient to meet assembly requirements.

A particular problem arises in the production of automotive display units. These units often include a multitude of components such as a speedometer, engine condition gauges, warning lights and information displays. Warning light and display components may be held by a moulded carrier affixed to a circuit board. Back-lighting may then be provided behind the carrier to illuminate a display or symbols printed on the carrier. With such display units, a liquid crystal display or light emitting diode may be offset from the circuit board by a distance, for example by mountings on the carrier. Electrical

connection pins then need to span to offset between the electronic components and the circuit board. It is then often necessary to insert long flexible connection pins into through-plated holes or a socket in the board.

5

It is difficult to automate such an assembly process because of the fragile nature of the pins, and the close tolerances needed to correctly insert a pin into a matching hole or socket, particularly when there are short  
10 production times. Manual assembly is relatively expensive and prone to errors. A pin may be bent or mis-inserted, leading to a faulty electronic assembly. Damaged sub-assemblies including a number of electrical components may be relatively expensive to re-work or to discard, leading  
15 to a certain wastage of components when parts become bent or broken during assembly.

If electrical connection pins are particularly long or flexible, it may be impractical to insert these into a  
20 matching socket, because of the tight fit required to make a good electrical connection. Long pins may be prone to bend upon insertion into a socket. Therefore, in some cases it is not possible to use a connecting socket, and the connection has to be made by soldering pins to the  
25 circuit board. It is generally desirable to use single-sided circuit boards, and surface-mounting techniques, to reduce cost. However, moulded carriers and sensitive electronic elements such as liquid crystal displays can be damaged by heat from soldering, which  
30 necessitates that soldered connections are made on the

side of the circuit board opposite the carrier or component. Since electrical connections may be required on the side of the board towards the carrier or display, for example for a surface mounted speedometer unit, this means  
5 that a double-sided board has to be used, thereby increasing cost.

It is an object of the invention to address these issues.

10 According to the invention there is provided a carrier for holding an electric component having one or more electrical connection pins, comprising a frame for holding the component, a pin guide, and a flexible portion connecting the pin guide to the frame, wherein:

15

a) the pin guide has one or more channels therethrough for receiving said electrical connection pins, the or each channel extending along a connection axis;

20 b) the frame has a base for mounting the carrier to a surface that extends transverse to the connection axis; and

c) the flexible portion is adapted to flex to allow the  
25 pin guide to move parallel to the connection axis when the pin guide is pressed in a direction along the connection axis.

It should be understood that a connection pin may be of a  
30 variety of cross sections, for example, circular, square

or rectangular.

The provision of a pin guide attached to the carrier may advantageously aid the location of the connection pin into  
5 a corresponding socket.

Preferably each connection pin extends into a corresponding channel in the pin guide. This helps each connection pin to be guided by the pin guide and therefore  
10 allows for easier location of a number pins at the same time.

Preferably each channel has an entrance into which an end of the corresponding pin is inserted when the electronic  
15 component is assembled to the carrier, and an exit from which the pin protrudes when the pin guide moves along the connection axis. The end of the pin is then protected within the channel when the electronic component is initially assembled to the carrier, and protrudes from the  
20 channel when the pin guide is moved along the connection axis.

This means that the pin is protected from accidental damage once assembled to the carrier. This will result in  
25 fewer connection pins being bent or broken prior to the assembly of the carrier and the circuit board. The fact that the pin protrudes from the end of the pin guide when the pin guide is moved along the connection axis enables the connection pins to be inserted into corresponding  
30 sockets on the circuit board.



The pin guide may have one or more protrusions that extend beyond the channel exit(s) in the direction of the connection axis. These protrusions can be used to aid in the accurate location of the pin guide with the respective socket on the circuit board.

Preferably the entrance to the channel is funnel-shaped to aid insertion of the corresponding pin. This means that the pin need only be aligned roughly with the pin guide prior to insertion of the pin into the channel. The funnel-shaped entrance into the channel will guide the pin into the respective channel.

Preferably the or each channel exit has a clearance fit with the corresponding pin to align the pin in orthogonal transverse directions to the connection axis when said pin protrudes from the exit. Therefore, the position of the pin with respect to the pin guide is accurately known when it protrudes from the pin guide. This will enable accurate alignment of the pins with the respective sockets on the circuit board.

Preferably the flexible portion is resiliently biased to a neutral position, and the end of the pin is fully retained in the channel when the flexible portion is in the neutral position. The pin guide then protects the pin prior to assembly of the carrier to the circuit board.

The flexible portion of the carrier may comprise a pair of

arms that extend generally transverse to the connection axis in opposite directions from the frame towards the pin guide. Such a symmetric construction of the flexible portion is useful as it constrains the pin guide to move  
5 along the connection axis without significant twisting or movement along other dimensions. This provides ease of manufacture for the component carrier. It is still possible, however, to provide sufficient compliance in the flexible portion to allow the pin guide to move slightly  
10 in other directions, which may be desirable to permit the pin guide to align with a matching connector.

The electronic component may be a planar display element, such as a liquid crystal display, with one or more  
15 connection pins extending from the element in a direction transverse to the plane of the element. The carrier is particularly useful in protecting such long pins and guiding them into a matching socket.

20 According to another aspect of the invention, there is provided a circuit board assembly, comprising an electronic assembly and a circuit board, the electronic assembly being mounted to the circuit board, and the electronic assembly being as described above, wherein the  
25 or each connection pin is electronically connected to a matching connection on the circuit board.

The circuit board assembly may include a socket, the socket being mounted on the circuit board and having one  
30 or more pin receptacles. The shape of the pin guide then

matches the shape of the socket so that the or each pin is automatically aligned with a corresponding pin receptacle as the electronic assembly is mounted to the circuit board. A benefit of this is that the electronic assembly  
5 may be mounted more easily as there is no need to align accurately the pins with the socket prior to assembly. Since this alignment occurs automatically, there is less chance of error and hence it is less likely that a component will be damaged during assembly.

10

The socket may protrude from the circuit board, and the pin guide may have a recess that matches the protrusion of the socket. This allows for easy automatic alignment of the pin guide with the socket.

15

The carrier and circuit board may have an alignment means by which the carrier is brought into approximate alignment with the circuit board as the electronic assembly is mounted to the circuit board. This promotes easier  
20 assembly of the electronic assembly and the circuit board, since only the carrier and board need to be brought into approximate alignment prior to assembly.

During mounting of the electronic assembly to the circuit  
25 board, the approximate alignment may be made before the pin guide comes into contact with the socket. This allows the pin guide to be approximately aligned with the socket automatically prior to the final accurate alignment of the pins with respective sockets.

30

The invention will now be further described, by way of example, with reference to the accompanying drawings, in which:

5        Figure 1 is a schematic perspective representation of an electronic component being inserted into a carrier according to the invention, the carrier having a flexible portion and a pin guide;

10       Figure 2 shows a schematic cross section view through the carrier and component taken along the line II-II of Figure 1, showing how pins on the electronic component align with channels through the pin guide when the component is inserted into the carrier; and

15       Figures 3, 4, 5 and 6 show views similar to that of Figure 2 of, respectively, the assembly of the component to the carrier, the initial approximate alignment of the carrier with a circuit board, the  
20       location of the pin guide with a socket on the circuit board, and the location of the pins in respective sockets.

Figure 1 shows a carrier 2 and an electronic component 4  
25       in the process of being assembled to the carrier. In this example, the component 4 is a liquid crystal display (LCD) 85mm long, 40mm wide and 2mm thick. The LCD 4 is generally planar in shape and has a number of long, flexible, straight connection pins 6 that extend from near the  
30       centre of a straight front edge 1 of the LCD 4 in a

direction perpendicular to the plane of the LCD. The carrier 2 has a generally planar top portion 5 with an upwardly facing surface 9 in which there is a centrally located recess 7 for receiving the LCD 4 in a snap-fit engagement. When LCD 4 is in engagement with the carrier 2, the LCD is flush with the planar top portion 5. Optionally the recess may include a back light (not shown) for illuminating the LCD 4.

10 A pair of skirts 18, 19 project downwards perpendicularly to the plane of the LCD 4 from two opposite side edges 13, 15 of the planar top portion 5. A rectangular hole 17 is provided through the planar top portion 5 near and parallel to the front edge 3 of the planar top portion 5  
15 to permit the LCD connection pins 6 to extend beneath the level of the upwardly facing surface when the LCD is engaged with the carrier 2. This movement is in the same direction as the length of the pins 6, and defines a connection axis 16. It should be understood that  
20 references to front and back refer only to the orientation of the carrier as shown in the drawings.

A substantially rectangular pin guide 8 is suspended from the planar top portion 5 below the hole 17 and located  
25 centrally between the skirts 18, 19 by a pair of intervening flexible portions 10. The flexible portions 10 extend from either side of the pin guide 8 in directions parallel to the front edge 3 of the planar top portion 5 and are attached near the front edge 3 at points on either  
30 side of the hole 17. The flexible portions 10 each have a

zig-zag bend 11 either side of the pin guide 8 to aid flexing along the connection axis 16. The carrier 2 also has two spike-shaped locator devices 12, 14 extending downwardly from the planar top portion 5 in a direction parallel to the connection axis 16. These locator devices 12, 14 are positioned behind the flexible portions 10 and extend beyond the skirts 18, 19.

Figure 2 shows a schematic cross section view through the carrier 2 and the LCD 4 taken along the line II-II of Figure 1. The drawing shows the general shape of a number of channels 20 through the pin guide 8 and how each one of the pins 6 lines up with a corresponding one of the channels 20 when the LCD 4 is about to be assembled to the carrier along the connection axis. Each channel 20 has a funnel-shaped entrance 22 that is wider than the pin 6 to facilitate entry of the pin 6 into the channel 20. The recess 7 provides an easy way to approximately align the LCD 4 with the carrier 2 prior to assembly and thus allow the pins 6 to be aligned approximately with the channel entrances 22 prior to assembly.

Each channel 20 narrows towards an exit 24 of the channel 20, the exit 24 being a clearance fit with the pin 6 such that each pin 6 is accurately positioned with respect to the pin guide 8 as each pin 6 approaches the corresponding pin guide exit 24, as shown in Figure 3.

In the present example, the pin guide 8 is rectangular in a cross-section parallel with the planar top portion 5,

and has a similarly rectangular base 28 extending around the pin exits 24. The pin guide base 28 is surrounded on its four sides by a downwardly protruding rim 26. The rim extends in the direction of the connection axis 16. This protrusion 26 is shaped to provide a wide opening which narrows upwardly towards the pin guide base 28 to facilitate the location and engagement of the pin guide 8 with a matching receiving socket 42 as shown in Figures 4, 5 and 6.

10

Figure 3 shows a cross section view similar to Figure 2, showing the LCD 4 assembled to the carrier 2, with the LCD 4 fully seated into the recess 17 in the planar top portion 5. This prevents movement of the component 4 relative to the carrier 2 and thus prevents damage to the pins 6, which are located within their respective channels 20.

Figure 4 shows the assembly of carrier 2 and LCD 4 onto a circuit board 40 with the socket 42 mounted on the circuit board. The circuit board 40 is located below the carrier 2 and parallel to the plane of the LCD 4 and the planar top portion 5. The approximate location of the carrier 2 and the circuit board 40 is achieved by moving the carrier 2 and the circuit board 40 together along the connection axis 16. The spike-shaped locator devices 12, 14 make contact first with the circuit board 40, and locate into respective matching holes 41 in the circuit board 40. The spiked shape of the locator devices 12, 14 allows for some error in the alignment of the carrier 2 with the board 40

30

prior to full assembly. Once the approximate alignment of the carrier 2 with the board 40 has been made by using the locator devices 12, 14 it can be seen that the pin guide 8 has been approximately aligned with the socket 42.

5

Figure 5 shows a further stage in the assembly of carrier 2 and LCD 4 to the circuit board 40. The accurate location of the pin guide 8 over the socket 42 has been achieved by the funnel-shaped protruding rim 26 on the pin guide  
10 locating the pin guide 8 over the socket 42 correctly. This alignment may include deflection of the flexible portions 10 to allow the pin guide 8 to move in directions transverse to the connection axis 16 so that the pin guide 8 may seat accurately over the socket 42. As a result of  
15 the accurate location the pin exits 24 from the channels 20 align with the corresponding entrances 52 and connection holes 54 in the socket 42.

Figure 6 shows the pins 6 fully inserted into the  
20 respective holes 54 in the socket 42. This has been achieved by the deflection of the flexible portion 10 of the component carrier 2 to allow the pin guide 8 to move in a direction along the connection axis 16 towards the planar top portion 5. This deflection is caused by a force  
25 applied to the pin guide 8 by the socket 42 in the direction of the connection axis 16. The skirts 18, 19 come into contact with the circuit board 40 and support the carrier 2 at a distance from the circuit board 40. This distance being sufficient to allow the pins 6 to  
30 enter the connection holes 54, but not be forced onto the



circuit board 40 causing possible bending or damage. The distance is also sufficient to permit an LCD backlight (not shown) to be provided on the board 40 or the carrier 2.

5

Optionally there may be provided on the skirts 18, 19, locator pins 12, 14 or other parts, means (not shown) to effect a "snap-fit" to the circuit board. This allows the carrier 2 and LCD 4 to be held to the board securely. The "snap-fit" preferably also allows the carrier to be removed easily from the circuit board and replaced with another if it is, for instance, found to be faulty. This will reduce the need to scrap a circuit board with many components already attached simply because one component is found to be faulty.

Although the invention has been described with specific reference to a liquid crystal display for an automobile dashboard display, the invention is equally applicable for use in mobile phones, pocket calculators, personal organisers, remote controls for audio-visual equipment or any other apparatus requiring an electrical connection pin to be fitted into a corresponding socket.

25

## Claims

1. A carrier for holding an electric component having a one or more electrical connection pins, comprising a frame for holding the component, a pin guide, and a flexible portion connecting the pin guide to the frame, wherein:
  - a) the pin guide has one or more channels therethrough for receiving said electrical connection pins, the or each channel extending along a connection axis;
  - b) the frame has a base for mounting the carrier to a surface that extends transverse to the connection axis;
  - c) the flexible portion is adapted to flex to allow the pin guide to move parallel to the connection axis when the pin guide is pressed in a direction along the connection axis.
2. An electronic assembly, comprising a carrier and an electronic component having one or more connection pins, the electronic component being assembled to the carrier and the carrier being as claimed in Claim 1, wherein the or each connection pin extends into a corresponding channel in the pin guide.
3. An electronic assembly as claimed in Claim 2, in which: the or each channel has an entrance into which an end of the corresponding pin is inserted when the electronic component is assembled to the carrier, and an exit from

which the pin protrudes when the pin guide is moves along the connection axis; and the end of the pin is protected within the channel when the electronic component is initially assembled to the carrier, and protrudes from the channel when the pin guide is moved along the connection axis.

4. An electronic assembly as claimed in Claim 3, in which the pin guide has one or more protrusions that extend beyond the channel exit(s) in the direction of the connection axis.

5. An electronic assembly as claimed in Claim 3 or Claim 4, in which the entrance to the channel is funnel-shaped to aid insertion of the corresponding pin.

6. An electronic assembly as claimed in any of Claims 2 to 5, in which the or each channel exit has a clearance fit with the corresponding pin to align the pin in orthogonal transverse directions to the connection axis when said pin protrudes from the exit.

7. An electronic assembly as claimed in any of Claims 2 to 6, in which the flexible portion is resiliently biased to a neutral position, and the end of the pin is fully retained in the channel when the flexible portion is in the neutral position.

8. An electronic assembly as claimed in of Claims 2 to 4, in which the flexible portion of the carrier comprises a

pair of arms that extend generally transverse to the connection axis in opposite directions from the frame towards the pin guide.

5 9. An electronic assembly as claimed in any of Claims 2 to 8, in which the electronic component is a planar display element with one or more connection pins extending from the element in a direction transverse to the plane of the element.

10

10. A circuit board assembly, comprising an electronic assembly and a circuit board, the electronic assembly being mounted to the circuit board, and the electronic assembly being as claimed in any of Claims 2 to 9, wherein  
15 the or each connection pin is electronically connected to a matching connection on the circuit board.

11. A circuit board assembly as claimed in Claim 10, including a socket, the socket being mounted on the  
20 circuit board and having one or more pin receptacles, in which the shape of the pin guide matches the shape of the socket so that the or each pin is automatically aligned with a corresponding pin receptacle as the electronic assembly is mounted to the circuit board.

25

12. A circuit board assembly as claimed in Claim 10, in which the socket protrudes from the circuit board, and the pin guide has a recess that matches the protrusion of the socket.

30

13. A circuit board assembly as claimed in Claim 11 or Claim 12, in which the carrier and circuit board have an alignment means by which the carrier is brought into approximate alignment with the circuit board as the electronic assembly is mounted to the circuit board.

14. A circuit board as claimed in Claim 13, in which during mounting of the electronic assembly to the circuit board, the approximate alignment is made before the pin guide comes into contact with the socket.

15. A carrier for holding an electric component, substantially as herein described, with reference to or as shown in the accompanying drawings.

16. An electronic assembly including a carrier for holding an electric component, substantially as herein described, with reference to or as shown in the accompanying drawings.



17. A circuit board assembly including a carrier for holding an electric component, substantially as herein described, with reference to or as shown in the accompanying drawings.

Abstract

This invention relates to a carrier for holding an  
5 electric component (4) having a one or more electrical  
connection pins (6), comprising a frame (2) for holding  
the component, a pin guide (8), and a flexible portion  
(10) connecting the pin guide to the frame. The pin guide  
having one or more channels through it for receiving the  
10 electrical connection pins (6). The frame having a base  
for mounting the carrier to a surface and the flexible  
portion being adapted to flex to allow the pin guide to  
move parallel to the connection axis (16) when the pin  
guide is pressed in a direction along the connection axis.

15

Figure 1



**THIS PAGE BLANK (USPTO)**






FIG 3






FIG 4

**THIS PAGE BLANK (USPTO)**



**THIS PAGE BLANK (USPTO)**